

Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 16.04.2025

Version number 2 (replaces version 1)

Revision: 16.04.2025

* SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Water saturated Phenol pH 4.5
- **Product Code:** 40-1100-20, 40-1100-04
- **Registration number** Mixture
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Product category** PC21 Laboratory chemicals
- **Application of the substance / the mixture** Laboratory chemicals
- **Uses advised against**
 - Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).
 - Any use involving aerosol formation or vapour release in excess of the assigned Workplace Exposure Limit where workers are exposed without suitable Respiratory Protective Equipment.
 - Processes involving extreme heat use advised against.
 - Processes involving the use of incompatible substances - refer to section 10.
 - Processes where workers who may be pregnant or breastfeeding could potentially come into direct contact with the undiluted product.
 - The product is strictly intended for industrial or professional use only.
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**
 - Severn Biotech Ltd.
 - Unit 2,
 - Park Lane,
 - Kidderminster,
 - Worcestershire.
 - DY11 6TJ
 - UK
 - Tel: 0044 1562 825286
 - Fax: 0044 1562 825284
 - email: info@severnbiotech.com
- **Further information obtainable from:** Product safety department.
- **1.4 Emergency telephone number:**
 - Members of the public seeking specific information on poisons should contact:
 - In England and Wales: NHS 111 - dial 111
 - In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to GB-CLP**

Acute Tox. 3	H301 Toxic if swallowed.
Acute Tox. 3	H311 Toxic in contact with skin.
Acute Tox. 3	H331 Toxic if inhaled.
Skin Corr. 1B	H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.
Muta. 2	H341 Suspected of causing genetic defects.
STOT RE 2	H373 May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 2	H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

— GB —

Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 16.04.2025

Version number 2 (replaces version 1)

Revision: 16.04.2025

Trade name: Water saturated Phenol pH 4.5

(Contd. of page 1)

· 2.2 Label elements

· **Labelling according to GB-CLP** The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms


· **Signal word** Danger

· Hazard-determining components of labelling:

phenol

· Hazard statements

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H314 Causes severe skin burns and eye damage.

H341 Suspected of causing genetic defects.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.





· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 108-95-2 EINECS: 203-632-7 Index number: 604-001-00-2 Reg.nr.: 01-2119471329-32-XXXX	phenol  Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331;  Muta. 2, H341; STOT RE 2, H373;  Skin Corr. 1B, H314;  Aquatic Chronic 2, H411 ATE: LD50 oral: 100.1 mg/kg LC50/4 h inhalative: 0.51 mg/l Specific concentration limits: Skin Corr. 1B; H314: C ≥ 3 % Skin Irrit. 2; H315: 1 % ≤ C < 3 % Eye Irrit. 2; H319: 1 % ≤ C < 3 %	50 – 100%
--	--	-----------

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 16.04.2025

Version number 2 (replaces version 1)

Revision: 16.04.2025

Trade name: Water saturated Phenol pH 4.5

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:**

Immediately remove any clothing soiled by the product.

In all cases of significant exposure the patient should be transferred to a hospital as soon as possible.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Personal protection for the First Aider.

Keep polyethylene glycol (Lutrol) and Ambubag available for first aider use.

· **After inhalation:**

In case of inhalation:

- Provide fresh air.

- In case of breathing difficulties administer oxygen.

- No mouth-to-mouth or mouth-to-nose resuscitation. Use respiratory bag or oxygen resuscitation apparatus.

- Do not leave patient unattended.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Remove contaminated shoes, socks and clothing whilst washing the affected skin with running water for 5 minutes.

Continuously rinse the affected parts of the body with polyethylene glycol (e.g. Lutrol) or with plenty of water, followed by washing with olive oil or edible oil (to remove the phenol component).

Take to a hospital immediately.

· **After eye contact:**

Check for and remove any contact lenses.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Call for a doctor immediately.

· **Information for doctor:**

No specific antidote therapy for phenol poisoning is known, therefore it is important to remove the phenol completely from the body surface and out of the body as quickly as possible.

In the case of inhalation, prophylactic treatment to prevent pulmonary oedema is of great importance.

Phenol causes strong caustic burns of the skin and mucous membranes due to its protein degenerating action. The skin initially discolours white, then red. After initial pain, local anaesthesia appears.

Absorptive poisoning by large amounts of phenol is possible through small affected skin regions; this can lead to paralysis of the central nervous system and strong depression of the body temperature.

Inhaling phenol vapours can lead to damage of the bronchial system and pulmonary oedema.

Systemic damage to kidneys, liver and heart as well as neuropsychiatric disturbances are produced.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

* SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

(Contd. on page 4)

GB

Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 16.04.2025

Version number 2 (replaces version 1)

Revision: 16.04.2025

Trade name: Water saturated Phenol pH 4.5

(Contd. of page 3)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Toxic.
In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Formation of toxic gases is possible during heating or in case of fire.
Can form explosive gas-air mixtures.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear fully protective suit.
Decontaminate protective clothing prior to removal.
- **Additional information**
Absorb gas/vapours with water spray.
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Particular danger of slipping on leaked/spilled product.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow to penetrate the ground/soil.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Contain and collect spillage with non-combustible, absorbent material e.g.sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Contaminated absorbent material may pose the same hazard as the spilt product.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Restrict the quantity stored at the work place.
Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form.
Safety showers and eye wash facilities should be available at the work area.
The product must only be handled by authorised, trained and experienced professionals under strictly controlled conditions.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
A first-aider must be in attendance whilst this product is being handled.
All area first-aiders must have been provided with specialist training in the treatment required for potential incidents involving this product.

(Contd. on page 5)

Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 16.04.2025

Version number 2 (replaces version 1)

Revision: 16.04.2025

Trade name: Water saturated Phenol pH 4.5

(Contd. of page 4)

- Prevent formation of aerosols.
- **Information about fire - and explosion protection:** Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - Prevent any seepage into the ground.
 - Store only in the original receptacle.
- **Information about storage in one common storage facility:**
 - Store away from oxidising agents.
 - Store away from foodstuffs.
 - Store away from metals.
 - Do not store together with textiles.
- **Further information about storage conditions:**
 - Protect from frost.
 - Store under lock and key and with access restricted to technical experts or their assistants only.
 - Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 6.1 A
- **7.3 Specific end use(s)** No further relevant information available.

* SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 108-95-2 phenol

WEL	Short-term value: 16 mg/m ³ , 4 ppm
	Long-term value: 7.8 mg/m ³ , 2 ppm
Sk	

· **DNELs**

CAS: 108-95-2 phenol

Oral	Long-term systemic effects	500 µg/kg bw/day (general population)
Dermal	Long-term systemic effects	0.5 mg/kg bw/day (general population)
		1.23 mg/kg bw/day (worker)
Inhalative	Long-term systemic effects	0.452 mg/m ³ (general population)
		8 mg/m ³ (worker)
	Short-term local effects	16 mg/m ³ (worker)

· **PNECs**

CAS: 108-95-2 phenol

Freshwater	7.7 µg/L
Freshwater - Intermittent releases	31 µg/L
Marine water	770 ng/L
Sewage Treatment Plant	2.1 mg/L
Sediment (freshwater)	91.5 µg/kg
Sediment (marine water)	9.15 µg/kg
Soil	136 µg/kg

- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 6)

Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 16.04.2025

Version number 2 (replaces version 1)

Revision: 16.04.2025

Trade name: Water saturated Phenol pH 4.5

(Contd. of page 5)

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Storing food in the working area is prohibited.

Ensure that washing facilities are available at the work place.

A safe system of work must be formulated and followed to ensure safe working with this product. Relevant workers must receive suitable and sufficient training and supervision.

Take note of assigned Workplace Exposure Limits.

Pregnant women should strictly avoid inhalation or skin contact.

Do not eat, drink, smoke or sniff while working.

Depending on the degree of exposure, periodic medical examination is suggested.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Ensure that eyewash stations and safety showers are close to the workstation location.

· **Respiratory protection:**

Handle product in a fume cupboard.

If fume cupboard is unavailable, use respirator with organic vapour cartridge.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

If respiratory protection is required, institute a complete respiratory protection program including selection, fit testing, training, maintenance and inspection.

· **Hand protection**



Protective gloves.

Use gloves tested and approved under appropriate government standards such as NIOSH (US) or EN374 (EU).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Neoprene gloves

PVC gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Break-through time: >75 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed goggles conforming to EN166.



Face shield/visor.

Use equipment tested and approved under appropriate government standards such as EN166 (EU) or NIOSH (US)

(Contd. on page 7)

Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 16.04.2025

Version number 2 (replaces version 1)

Revision: 16.04.2025

Trade name: Water saturated Phenol pH 4.5

(Contd. of page 6)

Use visor in combination with goggles.

Body protection:


Impervious protective clothing

Do not get on skin or clothing. Wear clothing and footwear that cannot be penetrated by the product. Suitable protective equipment may include: Chemical resistant boots, Chemical resistant apron, Full chemical protective suit with a hood, Chemical protective suit consisting of a jacket and trousers. The jacket should be buttoned up to the neck, sleeves sealed at the gloves, and trouser legs worn outside the boots. These precautions are required to prevent the clothing from accidentally trapping product against the skin.

- **Environmental exposure controls** Do not allow to enter drains, sewers or watercourses.
- **Risk management measures** The operators shall be instructed adequately.

* SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state	Liquid
· Colour:	Light yellow
· Odour:	Characteristic
· Odour threshold:	0.04ppm
· Melting point/freezing point:	15 °C
· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	79 °C
· Auto-ignition temperature:	> 250 °C
· Decomposition temperature:	Not determined.
· pH at 20 °C	4.5
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Fully miscible.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	23 hPa
· Density and/or relative density	
· Density at 20 °C:	1.06 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

NOTE: The physical data presented above are typical values and should not be construed as a specification.

· Appearance:

· Form:

Powder

· Important information on protection of health and environment, and on safety.

· Ignition temperature:

Product is not self-igniting.

(Contd. on page 8)

GB

Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 16.04.2025

Version number 2 (replaces version 1)

Revision: 16.04.2025

Trade name: Water saturated Phenol pH 4.5

(Contd. of page 7)

· Explosive properties:	Product does not present an explosion hazard.
· Solvent content:	
· VOC (EC)	80.00 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Not applicable
· Flammable gases	Not applicable
· Aerosols	Not applicable
· Oxidising gases	Not applicable
· Gases under pressure	Not applicable
· Flammable liquids	Not applicable
· Flammable solids	Not applicable
· Self-reactive substances and mixtures	Not applicable
· Pyrophoric liquids	Not applicable
· Pyrophoric solids	Not applicable
· Self-heating substances and mixtures	Not applicable
· Substances and mixtures, which emit flammable gases in contact with water	Not applicable
· Oxidising liquids	Not applicable
· Oxidising solids	Not applicable
· Organic peroxides	Not applicable
· Corrosive to metals	Not applicable
· Desensitised explosives	Not applicable

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
Decomposes on heating, producing toxic fumes.
- **10.3 Possibility of hazardous reactions**
Reacts violently with oxidising agents.
Reacts with isocyanates.
Reacts with aldehydes.
Reacts with catalysts.
Reacts with certain metals.
- **10.4 Conditions to avoid** Heat and static discharge.
- **10.5 Incompatible materials:**
Strong acids and oxidising agents
Strong bases.
Finely powdered metals.
Aldehydes
Substances specifically listed in section 10.3 as incompatible.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

GB

(Contd. on page 9)

Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 16.04.2025

Version number 2 (replaces version 1)

Revision: 16.04.2025

Trade name: Water saturated Phenol pH 4.5

(Contd. of page 8)

* SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- **Acute toxicity** Toxic if swallowed, in contact with skin or if inhaled.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	125.13 mg/kg (ATE)
Dermal	LD50	825 mg/kg (rat)
Inhalative	LC50/4 h	0.625 mg/l

CAS: 108-95-2 phenol

Oral	LD50	100.1 mg/kg (ATE)
Dermal	LD50	660 mg/kg (rat)

· Primary irritant effect:

· Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation Causes serious eye damage.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· Germ cell mutagenicity

Suspected of causing genetic defects.

· Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure Based on available data, the classification criteria are not met.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

· Subacute to chronic toxicity:

EFFECTS OF LONG-TERM OR REPEATED EXPOSURE: The substance may have effects on the liver and kidneys.

· Additional toxicological information:

ROUTES OF EXPOSURE: Serious local effects by all routes of exposure.

EFFECTS OF SHORT-TERM EXPOSURE: The product is corrosive to the eyes, the skin and the respiratory tract.

Corrosive on ingestion. May cause effects on the central nervous system.

Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

Excessive exposure can be fatal.

Inhalation may cause lung oedema, but only after initial corrosive effects on eyes and/or airways have become manifest. The symptoms of lung oedema often do not become manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation are therefore essential. Immediate administration of an appropriate inhalation therapy by a doctor or a person authorized by him/her, should be considered.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients are listed.

GB

(Contd. on page 10)

Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 16.04.2025

Version number 2 (replaces version 1)

Revision: 16.04.2025

Trade name: Water saturated Phenol pH 4.5

(Contd. of page 9)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 108-95-2 phenol

EC50 (96 h) | 3.1 mg/l (Bacteria)

- **12.2 Persistence and degradability** Readily biodegradable
- **12.3 Bioaccumulative potential** Product is not expected to bioaccumulate.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
 Must not reach sewage water or drainage ditch undiluted or unneutralised.
 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.

* SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Recommended Hierarchy of Controls:

- Minimise waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

· Uncleaned packaging:

· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Container remains hazardous when empty. Continue to observe all precautions.

Do not mix with other waste streams.

Disposal must be made according to official regulations.

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

— GB —

(Contd. on page 11)

Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 16.04.2025




Version number 2 (replaces version 1)

Revision: 16.04.2025

Trade name: Water saturated Phenol pH 4.5

(Contd. of page 10)

* SECTION 14: Transport information

· 14.1 UN number or ID number	UN2821
· ADR/RID/ADN, IMDG, IATA	
· 14.2 UN proper shipping name	UN2821 PHENOL SOLUTION, ENVIRONMENTALLY HAZARDOUS
· ADR/RID/ADN	PHENOL SOLUTION, MARINE POLLUTANT
· IMDG	PHENOL SOLUTION
· IATA	
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
	
· Class	6.1 (T1) Toxic substances.
· Label	6.1
· IMDG	
	
· Class	6.1 Toxic substances.
· Label	6.1
· IATA	
	
· Class	6.1 Toxic substances.
· Label	6.1
· 14.4 Packing group	II
· ADR/RID/ADN, IMDG, IATA	
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: phenol
· Marine pollutant:	No
· Special marking (ADR/RID/ADN):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Toxic substances.
· Hazard identification number (Kemler code):	60
· Hazchem Code:	2X
· EMS Number:	F-A,S-A
· Stowage Category	A

(Contd. on page 12)

Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 16.04.2025

Version number 2 (replaces version 1)

Revision: 16.04.2025

Trade name: Water saturated Phenol pH 4.5

(Contd. of page 11)

· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	Amounts up to 5kg or 5L per single or inner package do not require the Environmentally Hazardous mark in accordance with ADR 5.2.1.8.1 and IMDG 2.10.2.7.
· ADR/RID/ADN	
· Limited quantities (LQ)	100 ml
· Excepted quantities (EQ)	Code: E4 Maximum net quantity per inner packaging: 1 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	100 ml
· Excepted quantities (EQ)	Code: E4 Maximum net quantity per inner packaging: 1 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2821 PHENOL SOLUTION, 6.1, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Poisons Act

· Regulated explosives precursors

None of the ingredients are listed.

· Regulated poisons

CAS: 108-95-2 phenol

Listed

· Reportable explosives precursors

None of the ingredients are listed.

· Reportable poisons

CAS: 108-95-2 phenol

Listed

· Control Of Major Accident Hazards Regulations 2015 (COMAH)

- **Named dangerous substances - ANNEX I** None of the ingredients are listed.

· COMAH category

H2

E2

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 13)

Safety data sheet

according to UK REACH (SI 2020/1577) as amended

Printing date 16.04.2025

Version number 2 (replaces version 1)

Revision: 16.04.2025

Trade name: Water saturated Phenol pH 4.5

(Contd. of page 12)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H341 Suspected of causing genetic defects.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

· Training hints

This product should only be handled by workers who have received sufficient training in the safe handling and use of chemical products.

· Department issuing SDS: Product safety department.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Muta. 2: Germ cell mutagenicity – Category 2
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· * Data compared to the previous version altered.