

Page 1/13

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.07.2025 Version number 2 (replaces version 1) Revision: 21.07.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: MB Grade Formaldehyde 37%

· Product Code: 40-6000

· Registration number Mixture

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Product category PC21 Laboratory chemicals
- · Application of the substance / the mixture Laboratory chemicals
- · Uses advised against

Any use involving aerosol formation or vapour release in excess of the assigned Workplace Exposure Limit where workers are exposed without suitable Respiratory Protective Equipment.

Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).

Processes involving the use of incompatible substances - refer to section 10.

Processes involving extreme heat use advised against.

The product is strictly intended for industrial or professional use only.

· 1.3 Details of the supplier of the safety data sheet

· Supplier:

Severn Biotech Ltd.

Unit 2,

Park Lane,

Kidderminster,

Worcestershire.

DY11 6TJ

UK

Tel: 0044 1562 825286 Fax: 0044 1562 825284

email: info@severnbiotech.com

- · Further information obtainable from: Product safety department.
- · 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to GB-CLP

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 3 H311 Toxic in contact with skin.

Acute Tox. 2 H330 Fatal if inhaled.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Muta. 2 H341 Suspected of causing genetic defects.

Carc. 1B H350 May cause cancer.

STOT SE 1 H370 Causes damage to the central nervous system and the visual organs.

STOT SE 3 H335 May cause respiratory irritation.

(Contd. on page 2)



Page 2/13

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Version number 2 (replaces version 1) Revision: 21.07.2025 Printing date 21.07.2025

Trade name: MB Grade Formaldehyde 37%

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to GB-CLP The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms







GHS06 GHS05

Signal word Danger

· Hazard-determining components of labelling:

Formaldehyde

Methanol

· Hazard statements

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H330 Fatal if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H370 Causes damage to the central nervous system and the visual organs.

H335 May cause respiratory irritation.

· Precautionary statements

Do not breathe mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Aqueous solution of the subtance(s) listed below.

(Contd. on page 3)



Page 3/13

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.07.2025 Version number 2 (replaces version 1) Revision: 21.07.2025

Trade name: MB Grade Formaldehyde 37%

(Contd. of page 2)

· Dangerous components:		
CAS: 50-00-0 EINECS: 200-001-8 Index number: 605-001-00-5 Reg.nr.: 01-2119488953-20-XXXX	Formaldehyde Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Muta. 2, H341; Carc. 1B, H350; Skin Corr. 1B, H314; Skin Sens. 1A, H317 Note: B, D ATE: LD50 dermal: 300 mg/kg Specific concentration limits: Skin Corr. 1B; H314: C ≥ 25 % Skin Irrit. 2; H315: 5 % ≤ C < 25 % Eye Irrit. 2; H319: 5 % ≤ C < 25 % Skin Sens. 1; H317: C ≥ 0.2 % STOT SE 3; H335: C ≥ 5 %	25 – 50%
CAS: 67-56-1 EINECS: 200-659-6 Index number: 603-001-00-X Reg.nr.: 01-2119433307-44-XXXX	Methanol	10 – 25%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Personal protection for the First Aider.

· After inhalation:

In case of inhalation:

- Provide fresh air.
- In case of breathing difficulties administer oxygen.
- No mouth-to-mouth or mouth-to-nose resuscitation. Use respiratory bag or oxygen resuscitation apparatus.
- Do not leave patient unattended.

If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Chemical burns must be treated promptly by a physician.

May be absorbed through the skin. Seek medical advice.

· After eye contact:

Check for and remove any contact lenses.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Wash mouth out with water

Do not induce vomiting; call for medical help immediately.

If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

· Information for doctor:

Contains formaldehyde and methanol.

Inhalation of an aerosol of this substance may cause lung oedema.

(Contd. on page 4)



Page 4/13

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.07.2025 Version number 2 (replaces version 1) Revision: 21.07.2025

Trade name: MB Grade Formaldehyde 37%

(Contd. of page 3)

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

Stomach wash. Administration of 100 ml of a solution containing 2% ammonium carbonate and 20% urea.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

· For safety reasons unsuitable extinguishing agents: Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Combustible

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Vapours can travel to a distant source of ignition and flash back.

Formaldehyde

· 5.3 Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

· Additional information

Absorb gas/vapours with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep ignition sources away - no smoking.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Contain and collect spillage with non-combustible, absorbent material e.g.sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB



Page 5/13

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.07.2025 Version number 2 (replaces version 1) Revision: 21.07.2025

Trade name: MB Grade Formaldehyde 37%

(Contd. of page 4)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

The product must only be handled by authorised, trained and experienced professionals under strictly controlled conditions.

Conduct maintenance and other work on or in storage/reactor/mixing vessels or closed spaces ONLY under strict Permit to Work conditions.

Welding and other hot work operations in the work area must only be permitted under supervision.

Safety showers and eye wash facilities should be available at the work area.

· Information about fire - and explosion protection:

Protect from heat.

Keep respiratory protective device available.

Protect against electrostatic charges.

Keep ignition sources away - Do not smoke.

Flammable gas-air mixtures may form in empty receptacles.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Prevent any seepage into the ground.

Store only in the original receptacle.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store in a bunded area.

Protect from heat and direct sunlight.

· Storage class: 6.1 A

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 50-00-0 Formaldehyde

WEL Short-term value: 2.5 mg/m³, 2 ppm Long-term value: 2.5 mg/m³, 2 ppm

Carc

CAS: 67-56-1 Methanol

WEL Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm

Sk

(Contd. on page 6)



Page 6/13

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.07.2025 Version number 2 (replaces version 1) Revision: 21.07.2025

Trade name: MB Grade Formaldehyde 37%

(Contd. of page 5)

· DNELs		
	00-0 Formaldehyde	
	-	4.1 /I /1. /
Oral		4.1 mg/kg bw/day (general population)
Dermal	Long-term systemic effects	102 mg/kg bw/day (general population)
		240 mg/kg bw/day (worker)
	Long-term systemic effects	12 μg/kg bw/day (general population)
	Long-term local effects	37 μg/kg bw/day (worker)
Inhalative	Long-term systemic effects	3.2 mg/m³ (general population)
		9 mg/m³ (worker)
	Long-term local effects	100 μg/m³ (general population)
		375 μg/m³ (worker)
	Short-term local effects	750 μg/m³ (worker)
CAS: 67-5	56-1 Methanol	
Oral	Long-term systemic effects	4 mg/kg bw/day (general population)
	Short-term systemic effects	4 mg/kg bw/day (general population)
Dermal	Long-term systemic effects	4 mg/kg bw/day (general population)
		20 mg/kg bw/day (worker)
	Short-term systemic effects	4 mg/kg bw/day (general population)
	-	20 mg/kg bw/day (worker)
Inhalative	Long-term systemic effects	26 mg/m³ (general population)
		130 mg/m³ (worker)
	Short-term systemic effects	26 mg/m³ (general population)
	·	130 mg/m³ (worker)
	Long-term local effects	26 mg/m³ (general population)
		130 mg/m³ (worker)
	Short-term local effects	26 mg/m³ (general population)
		130 mg/m³ (worker)
		7.7 6 (0.7 17)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Pregnant women should strictly avoid inhalation or skin contact.

A safe system of work must be formulated and followed to ensure safe working with this product. Relevant workers must receive suitable and sufficient training and supervision.

Ensure that eyewash stations and safety showers are close to the workstation location.

Take note of assigned Workplace Exposure Limits.

Depending on the degree of exposure, periodic medical examination is suggested.

 $(Contd.\ on\ page\ 7)$



Page 7/13

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.07.2025 Version number 2 (replaces version 1) Revision: 21.07.2025

Trade name: MB Grade Formaldehyde 37%

(Contd. of page 6)

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A for organic vapours

· Hand protection



Protective gloves.

Use gloves tested and approved under appropriate government standards such as NIOSH (US) or EN374 (EU).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Break-through time: > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles conforming to EN166.



Face shield/visor.

Use equipment tested and approved under appropriate government stangards such as EN166 (EU) or NIOSH (US)

Use visor in combination with goggles.

· Body protection:



Impervious protective clothing

Do not get on skin or clothing. Wear clothing and footwear that cannot be penetrated by the product. Suitable protective equipment may include: Chemical resistant boots, Chemical resistant apron, Full chemical protective suit with a hood, Chemical protective suit consisting of a jacket and trousers. The jacket should be buttoned up to the neck, sleeves sealed at the gloves, and trouser legs worn outside the boots. These precautions are required to prevent the clothing from accidentally trapping product against the skin.

- · Environmental exposure controls Do not allow to enter drains, sewers or watercourses.
- · Risk management measures

The operators shall be instructed adequately.

The workplace shall be inspected regularly by competent personnel e.g. the safety representative.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state Liquid

(Contd. on page 8)



Page 8/13

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.07.2025 Version number 2 (replaces version 1) Revision: 21.07.2025

Trade name: MB Grade Formaldehyde 37%

(Contd. of page 7)

Colour:
Odour:
Odour threshold:

Colourless
Pungent
Not determined.

• Melting point/freezing point: ~ 0 °C

· Boiling point or initial boiling point and boiling range -21 °C

· Lower and upper explosion limit

Lower: 7 Vol %
 Upper: 73 Vol %
 Flash point: 62 °C
 Auto-ignition temperature: ~300 °C
 pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

water: Fully miscible.
Partition coefficient n-octanol/water (log value)
Vapour pressure at 20 °C: 23 hPa

· Density and/or relative density

• Density at 20 °C: 1.08 g/cm³

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

• **Ignition temperature:** Product is not self-igniting.

• Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Information with regard to physical hazard classes

Not applicable · Explosives Not applicable · Flammable gases Not applicable · Aerosols · Oxidising gases Not applicable · Gases under pressure Not applicable · Flammable liquids Not applicable · Flammable solids Not applicable · Self-reactive substances and mixtures Not applicable · Pyrophoric liquids Not applicable Not applicable · Pyrophoric solids Not applicable · Self-heating substances and mixtures

· Substances and mixtures, which emit flammable gases

in contact with water

Oxidising liquids

Oxidising solids

Organic peroxides

Corrosive to metals

Desensitised explosives

Not applicable

Not applicable

Not applicable

Not applicable



Page 9/13

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.07.2025 Version number 2 (replaces version 1) Revision: 21.07.2025

Trade name: MB Grade Formaldehyde 37%

(Contd. of page 8)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts violently with oxidising agents.

Exothermic reaction with acids.

Exothermic reaction with alkalis

- · 10.4 Conditions to avoid Heat and static discharge.
- · 10.5 Incompatible materials:

Substances specifically listed in section 10.3 as incompatible.

Strong acids.

Strong bases.

Strong oxidising agents.

· 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Formaldehyde

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Harmful if swallowed.

Toxic in contact with skin.

Fatal if inhaled.

· LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimates)		
Oral	LD50	595.9 mg/kg
Dermal	LD50	625 mg/kg
Inhalative	LC50/4 h	1.5017 mg/l

CAS: 50-00-0 Formaldehyde		
Oral	LD50	640 mg/kg (rat)
Inhalative	LC50/4 h	0.588 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

· Germ cell mutagenicity

Suspected of causing genetic defects.

· Carcinogenicity

May cause cancer.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

Causes damage to the central nervous system and the visual organs.



Page 10/13

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.07.2025 Version number 2 (replaces version 1) Revision: 21.07.2025

Trade name: MB Grade Formaldehyde 37%

(Contd. of page 9)

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Subacute to chronic toxicity:

Prolonged or repeated skin contact may irritate and cause dermatitis.

Repeated or prolonged inhalation exposure may cause asthma.

· Additional toxicological information:

ROUTES OF EXPOSURE: The component substances can variously be absorbed into the body by inhalation, through the skin and by ingestion.

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of oesophagus and stomach.

Inhalation may cause lung oedema, but only after initial corrosive effects on eyes and/or airways have become manifest. The symptoms of lung oedema often do not become manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation are therefore essential. Immediate administration of an appropriate inhalation therapy by a doctor or a person authorized by him/her, should be considered.

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

CAS: 50-00-0 Formaldehyde

EC50 (96 h) 14.7 mg/l (Bacteria)

- · 12.2 Persistence and degradability biodegradable
- · 12.3 Bioaccumulative potential Product is not expected to bioaccumulate.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Recommended Hierarchy of Controls:

- Minimise waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

(Contd. on page 11)



Page 11/13

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.07.2025 Version number 2 (replaces version 1) Revision: 21.07.2025

Trade name: MB Grade Formaldehyde 37%

(Contd. of page 10)

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Contact waste processors for recycling information.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

Do not mix with other waste streams.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Disposal must be made according to official regulations.

Container remains hazardous when empty. Continue to observe all precautions.

Containers, even those that are "empty," may contain residues that can develop flammable vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

Do not mix with other waste streams.

· Recommended cleansing agents: Large quantities of water

SECTION 14:	Transpor	t information
--------------------	----------	---------------

· 14.1 UN number or ID number · ADR/RID/ADN, IMDG, IATA	UN2922
· 14.2 UN proper shipping name · ADR/RID/ADN	UN2922 CORROSIVE LIQUID, TOXIC, N.O.S. (FORMALDEHYDE SOLUTION, METHANOL)
· IMDG, IATA	CORROSIVE LIQUID, TOXIC, N.O.S. (FORMALDEHYDE SOLUTION, METHANOL)

- · 14.3 Transport hazard class(es)
- · ADR/RID/ADN





• Class 8 (CT1) Corrosive substances. • Label 8+6.1

· IMDG





· Class 8 Corrosive substances. · Label 8/6.1

· IATA





· Class· Label8 Corrosive substances.8 (6.1)

(Contd. on page 12)



Page 12/13

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.07.2025 Version number 2 (replaces version 1) Revision: 21.07.2025

Trade name: MB Grade Formaldehyde 37%

(Contd. of p

	` 10
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	III
145D 1 411 1	
14.5 Environmental hazards:	Y
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Corrosive substances.
· Hazard identification number (Kemler code):	86
Hazchem Code:	2X
· EMS Number:	F-A,S-B
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.
· 14.7 Maritime transport in bulk according to IM	0
instruments	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Tuomanantaataaan	
Transport category	3
· Tunnel restriction code	Е
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
(- t)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
	2 22 2 2
· UN "Model Regulation":	UN 2922 CORROSIVE LIQUID, TOXIC, N.O.S.
	(FORMALDEHYDE SOLUTION, METHANOL), 8 (6.1), III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act	
· Regulated explosives precursors	

None of the ingredients are listed.

· Regulated poisons

None of the ingredients are listed.

· Reportable explosives precursors

None of the ingredients are listed.

· Reportable poisons

CAS: 50-00-0 Formaldehyde

5%

- · Control Of Major Accident Hazards Regulations 2015 (COMAH)
- · Named dangerous substances ANNEX I None of the ingredients are listed.
- · COMAH category H2



Page 13/13

Safety Data Sheet according to UK REACH (SI 2020/1577) as amended

Printing date 21.07.2025 Version number 2 (replaces version 1) Revision: 21.07.2025

Trade name: MB Grade Formaldehyde 37%

(Contd. of page 12)

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H370 Causes damage to organs.

H371 May cause damage to organs.

· Training hints

This product should only be handled by workers who have received sufficient training in the safe handling and use of chemical products.

· Department issuing SDS: Product safety department.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Muta. 2: Germ cell mutagenicity – Category 2

Carc. 1B: Carcinogenicity – Category 1B

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

* Data compared to the previous version altered.